



## THE JAMPRO LOW POWER FM BROADCAST ANTENNA

The JAMPRO JLPC antenna is the low power version of the popular PENETRATOR antenna, which has become an industry standard for quality and performance. Each bay consists of a PENETRATOR style radiating element with a rigid shunt feed line supported by a galvanized steel mounting bracket; standard round leg mounting brackets for a uniform face tower are included with each antenna. Silver plated inner conductor connectors are used throughout for maximum contact life and minimum power loss. Outstanding Performance for HD Radio, Stereo and SCA Operation. Excellent VSWR and Bandwidth 1.1:1 +/- 150 KHz typical



**Reduced RF Arrays**

**Pattern Measurement Study**

**Custom Mounting Brackets Available**

**Electrical Beam Tilt**

**Null Fill**

**Rugged Mechanical Construction**

**Mounting True Circular Polarization**

**Range 88-108 MHz**

**DC Grounded at Each Bay for Lighting Protection**

**Marine Brass & Copper for Longevity**



# Bays	Power Gain	dB Gain	FS @ 1 Mi.	Safe Input Power kW	Weight (lbs)	Wind load (lbs)
1	0.46	-3.37	93.2	1	Contact Factory	
2	1.00	0.00	136.7	2		
3	1.50	1.76	168.4	3		
4	2.10	3.22	199.2	4		
5	2.70	4.31	225.2	4		
6	3.20	5.05	246.0	4		
8	4.30	6.34	285.2	4		
10	5.50	7.40	322.4	4		
12	6.60	8.20	353.2	4		

- Notes:**
- Weights and wind loads contact factory.
  - Wind loads based on 50/33 PSF (98 MHz, midband)
  - Feed points, when end fed is 3 ft below bottom bay; when center fed is 9'. 6" below center
  - All inputs are EIA flange, female
  - Power derating occurs above 2,000 feet elevation. Contact factory for details
  - Power and Db gains are typical for horizontal and vertical components
  - Special mounting brackets are available
  - Other combinations of EIA inputs and power ratings available
  - Free space azimuth circularity is  $\pm 2.0$  dB
  - Polarization is right hand, clockwise circular
  - Power gain is based on half wave dipole in free space

Since many factors contribute to a station's compliance with the FCC exposure guidelines for radio frequency radiation, JAMPRO ANTENNAS, INC. cannot accept any responsibility in this matter. The station must examine and determine its status based on each individual situation. For reduced low angle radiation near the tower, a low RFR model of this antenna is available. Contact the factory for pricing data and further details.

\*All specifications are subject to change without notice.